



# 外法一定H形鋼




寸法 mm			質量 kg/m	断面積 cm <sup>2</sup>	断面2次モーメント cm <sup>4</sup>		断面2次半径 cm		断面係数 cm <sup>3</sup>		
A×B	t <sub>1</sub>	t <sub>2</sub>			r	I <sub>x</sub>	I <sub>y</sub>	i <sub>x</sub>	i <sub>y</sub>	Z <sub>x</sub>	Z <sub>y</sub>
650×200	9	12	13	83.1	105.8	68,600	1,600	25.5	3.89	2,110	160
	9	16	13	95.1	121.1	83,400	2,140	26.2	4.20	2,570	214
	9	19	13	104	132.5	94,200	2,540	26.7	4.38	2,900	254
	9	22	13	113	144.0	105,000	2,940	27.0	4.52	3,220	294
	12	19	13	118	150.9	99,900	2,540	25.7	4.11	3,070	254
	12	22	13	127	162.2	110,000	2,940	26.1	4.26	3,400	294
	12	25	13	136	173.4	121,000	3,340	26.4	4.39	3,710	334
	12	28	13	145	184.7	131,000	3,740	26.6	4.50	4,020	374
650×250	12	19	13	133	169.5	119,000	4,960	26.4	5.40	3,660	397
	12	22	13	145	184.2	132,000	5,740	26.8	5.58	4,060	459
	12	25	13	156	198.4	145,000	6,520	27.0	5.73	4,460	522
	12	28	13	167	212.7	158,000	7,300	27.2	5.86	4,850	584
	16	28	13	186	236.5	165,000	7,310	26.4	5.56	5,070	585
700×200	9	12	18	87.6	111.6	83,100	1,610	27.3	3.79	2,370	161
	9	16	18	99.6	126.9	100,000	2,140	28.1	4.11	2,860	214
	9	19	18	109	138.4	113,000	2,540	28.6	4.28	3,220	254
	9	22	18	118	149.8	125,000	2,940	28.9	4.43	3,580	294
	12	22	18	133	169.5	132,000	2,950	27.9	4.17	3,780	295
	12	25	18	142	180.8	144,000	3,350	28.3	4.30	4,120	335
	12	28	18	151	192.1	156,000	3,750	28.5	4.42	4,460	375
700×250	9	16	18	112	142.9	119,000	4,170	28.9	5.40	3,400	334
	9	19	18	124	157.4	135,000	4,950	29.3	5.61	3,850	396
	12	19	18	139	177.2	142,000	4,960	28.3	5.29	4,060	397
	12	22	18	150	191.5	158,000	5,740	28.7	5.48	4,500	459
	12	25	18	162	205.8	173,000	6,520	29.0	5.63	4,940	522
	14	25	18	172	218.8	177,000	6,530	28.5	5.46	5,070	522
	14	28	18	183	232.9	192,000	7,310	28.7	5.60	5,490	585

切断・穴孔・ショット・開先加工も承ります。



寸法 mm				質量 kg/m	断面積 cm <sup>2</sup>	断面2次モーメント cm <sup>4</sup>		断面2次半径 cm		断面係数 cm <sup>3</sup>	
A×B	t <sub>1</sub>	t <sub>2</sub>	r			I <sub>x</sub>	I <sub>y</sub>	i <sub>x</sub>	i <sub>y</sub>	Z <sub>x</sub>	Z <sub>y</sub>
700×300	12	19	18	154	196.2	164,000	8,560	28.9	6.61	4,690	571
	12	22	18	168	213.5	183,000	9,910	29.3	6.81	5,230	661
	12	25	18	181	230.8	201,000	11,300	29.1	6.80	5,880	751
	14	25	18	191	243.8	206,000	11,300	29.1	6.80	5,880	751
	14	28	18	205	260.9	224,000	12,600	29.3	6.95	6,390	841
	16	28	18	215	273.8	228,000	12,600	28.9	6.79	6,520	842
700×350 (SH)	12	22	18	185	235.5	208,000	15,700	29.7	8.17	5,950	899
	12	25	18	201	255.8	230,000	17,900	30.0	8.36	6,560	1,020
	14	22	18	195	248.6	213,000	15,700	29.3	7.96	6,080	899
	14	25	18	211	268.8	234,000	17,900	29.5	8.16	6,700	1,020
	14	28	18	227	288.9	255,000	20,000	29.7	8.33	7,300	1,140
	14	32	18	248	315.8	283,000	22,900	29.9	8.51	8,080	1,310
	16	25	18	221	281.8	239,000	17,900	29.1	7.97	6,830	1,020
	16	28	18	237	301.8	260,000	20,000	29.3	8.15	7,420	1,140
	16	32	18	258	328.5	287,000	22,900	29.6	8.35	8,200	1,310
	16	36	18	279	355.3	314,000	25,800	29.7	8.51	8,960	1,470
750×250	12	19	18	144	183.2	166,000	4,960	30.1	5.20	4,440	397
	12	22	18	155	197.5	184,000	5,740	30.6	5.39	4,920	459
	12	25	18	166	211.8	202,000	6,520	30.9	5.55	5,390	522
	14	25	18	177	225.8	208,000	6,530	30.3	5.38	5,540	522
	14	28	18	188	239.9	225,000	7,310	30.6	5.52	5,990	585


切断・穴孔・ショット・開先加工も承ります。



寸法 mm				質量 kg/m	断面積 cm <sup>2</sup>	断面2次モーメント cm <sup>4</sup>		断面2次半径 cm		断面係数 cm <sup>3</sup>	
A×B	t <sub>1</sub>	t <sub>2</sub>	r			I <sub>x</sub>	I <sub>y</sub>	i <sub>x</sub>	i <sub>y</sub>	Z <sub>x</sub>	Z <sub>y</sub>
750×300 (SH)	14	22	18	183	233.6	219,000	9,920	30.6	6.52	5,850	661
	14	25	18	197	250.8	241,000	11,300	31.0	6.70	6,410	751
	14	28	18	210	267.9	261,000	12,600	31.2	6.86	6,970	841
	16	25	18	208	264.8	246,000	11,300	30.5	6.53	6,570	752
	16	28	18	221	281.8	267,000	12,600	30.8	6.69	7,120	842
	16	32	18	239	304.5	294,000	14,400	31.1	6.88	7,840	962
750×350 (SH)	14	25	18	217	275.8	273,000	17,900	31.5	8.05	7,290	1,020
	14	28	18	232	295.9	298,000	20,000	31.7	8.23	7,940	1,140
	14	32	18	253	322.8	330,000	22,900	32.0	8.42	8,790	1,310
	16	28	18	243	309.8	303,000	20,000	31.3	8.04	8,090	1,140
	16	32	18	264	336.5	335,000	22,900	31.6	8.25	8,940	1,310
	16	36	18	285	363.3	366,000	25,800	31.7	8.42	9,760	1,470
800×250	14	22	18	172	218.6	221,000	5,750	31.8	5.13	5,520	460
	14	25	18	183	232.8	241,000	6,530	32.2	5.30	6,020	523
	16	25	18	195	247.8	248,000	6,540	31.6	5.14	6,200	523
	16	28	18	206	261.8	267,000	7,320	32.0	5.29	6,680	586
800×300	14	22	18	189	240.6	254,000	9,920	32.5	6.42	6,350	661
	14	25	18	202	257.8	278,000	11,300	32.9	6.61	6,960	751
	14	28	18	216	274.9	302,000	12,600	33.2	6.78	7,560	841
	16	22	18	201	255.7	261,000	9,930	32.0	6.23	6,530	662
	16	25	18	214	272.8	285,000	11,300	32.3	6.43	7,130	752
	16	28	18	227	289.8	309,000	12,600	32.7	6.60	7,730	842
	16	32	18	245	312.5	340,000	14,400	33.0	6.79	8,500	962


切断・穴孔・ショット・開先加工も承ります。






寸法 mm				質量 kg/m	断面積 cm <sup>2</sup>	断面2次モーメント cm <sup>4</sup>		断面2次半径 cm		断面係数 cm <sup>3</sup>	
A×B	t <sub>1</sub>	t <sub>2</sub>	r			I <sub>x</sub>	I <sub>y</sub>	i <sub>x</sub>	i <sub>y</sub>	Z <sub>x</sub>	Z <sub>y</sub>
800×350 (SH)	14	25	18	222	282.8	316,000	17,900	33.4	7.95	7,900	1,020
	14	28	18	238	302.9	344,000	20,000	33.7	8.13	8,600	1,140
	16	25	18	234	297.8	323,000	17,900	32.9	7.75	8,070	1,020
	16	28	18	249	317.8	351,000	20,000	33.2	7.94	8,770	1,150
	16	32	18	270	344.5	387,000	22,900	33.5	8.15	9,680	1,310
	16	36	18	291	371.3	423,000	25,800	33.8	8.33	10,600	1,470
	19	25	18	251	320.3	333,000	17,900	32.3	7.48	8,340	1,020
	19	28	18	267	340.1	361,000	20,100	32.6	7.68	9,030	1,150
	19	32	18	288	366.6	397,000	22,900	32.9	7.91	9,930	1,310
	19	36	18	309	393.1	433,000	25,800	33.2	8.10	10,800	1,470
19	40	18	329	419.6	467,000	28,600	33.9	9.31	11,700	1,640	
800×400 (SH)	14	25	18	242	307.8	353,000	26,700	33.9	9.31	8,840	1,330
	14	28	18	260	330.9	386,000	29,900	34.1	9.50	9,640	1,490
	16	25	18	253	322.8	360,000	26,700	33.4	9.09	9,010	1,330
	16	28	18	271	345.8	393,000	29,900	33.7	9.30	9,810	1,490
	16	32	18	296	376.5	435,000	34,200	34.0	9.53	10,900	1,710
	16	36	18	320	407.3	476,000	38,400	34.2	9.71	11,900	1,920
	19	28	18	289	368.1	403,000	29,900	33.1	9.01	10,100	1,500
	19	32	18	313	398.6	445,000	34,200	33.4	9.26	11,100	1,710
	19	36	18	337	429.1	485,000	38,400	33.6	9.47	12,100	1,920
	19	40	18	361	459.6	525,000	42,700	33.8	9.64	13,100	2,140
850×250	14	22	18	177	225.6	254,000	5,750	33.6	5.05	5,980	460
	14	25	18	188	239.8	277,000	6,530	34.0	5.22	6,510	523
	16	25	18	201	255.8	285,000	6,540	33.4	5.06	6,720	523
	16	28	18	212	269.8	308,000	7,320	33.8	5.21	7,240	586
850×300	16	22	18	207	263.7	301,000	9,930	33.8	6.14	7,070	662
	16	25	18	220	280.8	328,000	11,300	34.2	6.34	7,720	752
	16	28	18	234	297.8	355,000	12,600	34.5	6.51	8,350	842
	16	32	18	252	320.5	390,000	14,400	34.9	6.71	9,180	962
850×350 (SH)	16	25	18	240	305.8	370,000	17,900	34.8	7.65	8,720	1,020
	16	28	18	256	325.8	402,000	20,000	35.1	7.84	9,460	1,150
	16	32	18	277	352.8	444,000	22,900	35.5	8.06	10,400	1,310
	19	28	18	274	349.6	415,000	20,100	34.4	7.57	9,760	1,150
	19	32	18	295	376.1	456,000	22,900	34.8	7.81	10,700	1,310
	19	36	18	316	402.6	496,000	25,800	35.1	8.00	11,700	1,470
	19	40	18	337	429.1	536,000	28,600	35.3	8.17	12,600	1,640

切断・穴孔・ショット・開先加工も承ります。



寸法 mm				質量 kg/m	断面積 cm <sup>2</sup>	断面2次モーメント cm <sup>4</sup>		断面2次半径 cm		断面係数 cm <sup>3</sup>	
A×B	t <sub>1</sub>	t <sub>2</sub>	r			I <sub>x</sub>	I <sub>y</sub>	i <sub>x</sub>	i <sub>y</sub>	Z <sub>x</sub>	Z <sub>y</sub>
850×400 (SH)	16	25	18	260	330.8	413,000	26,700	35.3	8.98	9,720	1,330
	16	28	18	278	353.8	450,000	29,900	35.6	9.19	10,600	1,490
	16	32	18	302	384.5	497,000	34,200	36.0	9.43	11,700	1,710
	19	28	18	296	377.6	462,000	29,900	35.0	8.90	10,900	1,500
	19	32	18	320	408.1	510,000	34,200	35.3	9.15	12,000	1,710
	19	36	18	344	438.6	556,000	38,400	35.6	9.36	13,100	1,920
	19	40	18	368	469.1	602,000	42,700	35.8	9.54	14,200	2,140
900×250	16	19	18	185	235.7	275,000	4,980	34.1	4.60	6,110	399
	16	22	18	196	249.7	301,000	5,760	34.7	4.80	6,680	461
	16	25	18	207	263.8	326,000	6,540	35.2	4.98	7,250	524
	16	28	18	218	277.8	351,000	7,320	35.6	5.13	7,810	586
900×300	16	19	18	200	254.7	312,000	8,580	35.0	5.81	6,930	572
	16	22	18	213	271.7	343,000	9,930	35.5	6.05	7,620	662
	16	25	18	227	288.8	374,000	11,300	36.0	6.25	8,310	752
	16	28	18	240	305.8	404,000	12,600	36.4	6.43	8,990	842
	16	32	18	258	328.5	444,000	14,400	36.8	6.63	9,880	962
	19	25	18	247	314.3	389,000	11,300	35.2	6.00	8,650	754
	19	28	18	260	331.1	420,000	12,700	35.6	6.18	9,320	844
	19	32	18	278	353.6	459,000	14,500	36.0	6.39	10,200	964
900×350 (SH)	16	25	18	246	313.8	422,000	17,900	36.7	7.55	9,370	1,020
	16	28	18	262	333.8	458,000	20,000	37.0	7.75	10,200	1,150
	16	32	18	283	360.5	505,000	22,900	37.4	7.97	11,200	1,310
	19	25	18	266	339.3	437,000	17,900	35.9	7.27	9,720	1,020
	19	28	18	282	359.1	473,000	20,100	36.3	7.47	10,500	1,150
	19	32	18	303	385.6	519,000	22,900	36.7	7.71	11,500	1,310
	19	36	18	323	412.1	565,000	25,800	37.0	7.91	12,600	1,470
	19	40	18	344	438.6	610,000	28,600	37.3	8.08	13,600	1,640
900×400 (SH)	16	25	18	266	338.8	470,000	26,700	37.2	8.88	10,400	1,340
	16	28	18	284	361.8	511,000	29,900	37.6	9.09	11,400	1,490
	16	32	18	308	392.5	565,000	34,200	37.9	9.33	12,600	1,710
	19	28	18	304	387.1	526,000	29,900	36.9	8.79	11,700	1,500
	19	32	18	328	417.6	580,000	34,200	37.3	9.05	12,900	1,710
	19	36	18	352	448.1	632,000	38,500	37.6	9.26	14,100	1,920
	19	40	18	376	478.6	684,000	42,700	37.8	9.45	15,200	2,140

切断・穴孔・ショット・開先加工も承ります。



寸法 mm				質量 kg/m	断面積 cm <sup>2</sup>	断面2次モーメント cm <sup>4</sup>		断面2次半径 cm		断面係数 cm <sup>3</sup>		鋼種	幅厚比種別		塑性断面係数 cm <sup>3</sup>	
A×B	t <sub>1</sub>	t <sub>2</sub>	r			I <sub>x</sub>	I <sub>y</sub>	I <sub>x</sub>	I <sub>y</sub>	Z <sub>x</sub>	Z <sub>y</sub>		柱	梁	Z <sub>px</sub>	Z <sub>py</sub>
1000×300 (SH)	16	22	18	226	287.7	438,000	9,940	39.0	5.88	8,770	662	SN400	FD	FA	10,200	1,050
				SN490	FD	FC										
	16	25	18	239	304.8	477,000	11,300	39.6	6.09	9,540	752	SN400	FD	FA	11,100	1,190
				SN490	FD	FC										
	16	28	18	253	321.8	515,000	12,600	40.0	6.27	10,300	842	SN400	FD	FA	11,900	1,320
				SN490	FD	FC										
	16	32	18	270	344.5	565,000	14,400	40.5	6.47	11,300	962	SN400	FD	FA	12,900	1,500
				SN490	FD	FC										
19	25	18	262	333.3	498,000	11,300	38.7	5.83	9,970	754	SN400	FD	FA	11,700	1,210	
			SN490	FD	FA											
19	28	18	275	350.1	536,000	12,700	39.1	6.01	10,700	844	SN400	FD	FA	12,500	1,350	
			SN490	FD	FA											
19	32	18	292	372.6	586,000	14,500	39.6	6.23	11,700	964	SN400	FD	FA	13,600	1,530	
			SN490	FD	FA											
19	36	18	310	395.1	634,000	16,300	40.1	6.41	12,700	1,080	SN400	FD	FA	14,600	1,710	
			SN490	FD	FA											
1000×350 (SH)	16	22	18	243	309.7	491,000	15,800	39.8	7.13	9,820	900	SN400	FD	FA	11,300	1,410
				SN490	FD	FC										
	16	25	18	259	329.8	536,000	17,900	40.3	7.37	10,700	1,020	SN400	FD	FA	12,300	1,600
				SN490	FD	FC										
	16	28	18	275	349.8	581,000	20,000	40.8	7.57	11,600	1,150	SN400	FD	FA	13,200	1,780
				SN490	FD	FC										
	16	32	18	296	376.5	640,000	22,900	41.2	7.80	12,800	1,310	SN400	FD	FA	14,500	2,020
				SN490	FD	FC										
19	25	18	281	358.3	558,000	17,900	39.5	7.07	11,200	1,020	SN400	FD	FA	12,900	1,620	
			SN490	FD	FA											
19	28	18	297	378.1	602,000	20,100	39.9	7.28	12,000	1,150	SN400	FD	FA	13,900	1,800	
			SN490	FD	FA											
19	32	18	318	404.6	661,000	22,900	40.4	7.53	13,200	1,310	SN400	FD	FA	15,100	2,050	
			SN490	FD	FA											
19	36	18	338	431.1	718,000	25,800	40.8	7.73	14,400	1,470	SN400	FD	FA	16,400	2,290	
			SN490	FD	FA											

※1) サイズ表示例：SH-1000X350X19X36