

大径角形鋼管(コラム) 一般構造用角形鋼管 STKR400 JIS G3466 (1988) 製法ロールフォーミング

サイズ		質量	断面積	断面2次モーメント	断面係数	断面2次半径
A×B	厚さ mm	kg/m	cm ² (A)	cm ⁴ (I)	cm ³ (i)	cm(z)
200×200	4.5	27.2	34.67	2,190	219	7.95
	6	35.8	45.63	2,830	283	7.88
	8	46.9	59.79	3,620	362	7.78
	9	52.3	66.67	3,990	390	7.73
	12	67.9	86.53	4,980	498	7.59
250×250	6	45.2	57.63	5,670	454	9.92
	9	66.5	84.67	8,090	647	9.78
	12	86.8	110.5	10,300	820	9.63
	16	112	143.2	12,800	1,020	9.44
300×300	6	54.7	69.63	9,960	664	12.0
	9	80.6	102.7	14,300	956	11.8
	12	106	134.5	18,300	1,220	11.7
	16	138	175.2	23,100	1,840	11.5
	19	160	204.2	26,243	2,117	11.3
350×350	9	94.7	120.7	23,200	1,320	13.9
	12	124	158.5	29,800	1,700	13.7
	16	163	202.8	36,500	2,090	13.4
	19	190	242.2	43,357	2,477	13.3
	22	217	276.1	48,354	2,763	13.2
400×400	9	109	138.7	35,100	2,020	15.9
	12	143	182.5	45,300	2,640	15.8
	16	188	239.2	57,900	2,810	15.6
	19	220	280.2	66,644	3,332	15.4
	22	251	320.1	74,707	3,735	15.2
	※25	282	359.3	82,200	4,110	15.1
450×450	9	122	155.3	49,700	2,210	17.9
	12	162	206.5	65,433	2,908	17.7
	16	213	271.1	84,067	3,736	17.6
	19	250	318.2	97,055	4,313	17.4
	22	286	364.1	109,219	4,854	17.3
	※25	321	409.3	121,000	5,360	17.2
500×500	12	181	230.5	90,752	3,630	19.8
	16	238	303.1	117,050	4,682	19.6
	19	280	356.2	135,537	5,421	19.5
	22	320	408.1	152,992	6,119	19.3
	※25	361	459.3	169,000	6,780	19.2
550×550	16	263	335.2	158,000	5,730	21.7
	19	310	394.3	183,000	6,660	21.5
	22	355	452.2	207,000	7,530	21.4
	※25	400	509.3	230,000	8,360	21.3

切断・開先加工も承ります。