

# 配管用アーク溶接炭素鋼鋼管 STPY400 JIS G3457

呼称	外径 mm	厚さ mm	質量 kg/m	1本当り重量	
				6m	12m
350A	355.6	6.0	51.7	310	
		6.4	55.1	331	
		7.9	67.7	406	
		12.7	107	642	
400A	406.4	6.0	59.2	355	
		6.4	63.1	379	757
		7.9	77.6	466	931
		9.5	93.0	558	
		12.7	123	738	
450A	457.2	6.0	66.8	401	
		6.4	71.1	427	853
		7.9	87.5	525	1,050
		9.5	105	630	
		12.7	139	834	
500A	508.0	6.0	74.3	446	
		6.4	79.2	475	950
		7.9	97.4	584	1,169
		9.5	117	702	
		12.7	155	930	
550A	558.8	6.4	87.2	523	1,046
		7.9	107	642	1,284
		9.5	129	774	1,548
		12.7	171	1,026	2,052
600A	609.6	6.0	89.3	536	
		6.4	95.2	571	1,142
		7.9	117	702	1,404
		9.5	141	846	1,692
		12.7	187	1,122	2,244

呼称	外径 mm	厚さ mm	質量 kg/m	1本当り重量	
				6m	12m
650A	660.4	6.4	103	618	1,236
		7.9	127	762	1,524
		9.5	152	912	1,824
700A	711.2	6.0	104	624	
		6.4	111	666	1,332
		7.9	137	822	1,644
		9.5	164	984	1,968
		12.7	219	1,314	2,628
750A	762.0	7.9	147	882	1,764
		9.5	176	1,056	2,112
		12.7	235	1,410	2,820
800A	812.8	7.1	141	846	
		8.0	159	954	1,908
		9.5	188	1,128	2,256
900A	914.4	12.7	251	1,506	3,012
		8.0	179	1,074	2,148
		9.5	212	1,272	2,544
1000A	1016.0	12.7	282	1,692	3,384
		9.0	223	1,338	2,676
		9.5	236	1,416	2,832
1100A	1117.6	10.3	255	1,530	3,060
		12.7	314	1,884	3,768
		10.3	273	1,638	3,276
1200A	1219.2	9.5	283	1,698	3,396
		11.1	331	1,986	3,972
		12.7	378	2,268	4,536