

ガス管 配管用炭素鋼鋼管 SGP JIS G3452(1988)

JIS 呼称 記号 A	インチ名 記号 B	外径 mm	厚さ mm	質量 kg/m	1 本当り kg/5.5m
6A	1/8 B	10.5	2.0	0.419	2.30
8A	1/4 B	13.8	2.3	0.652	3.59
10A	3/8 B	17.3	2.3	0.851	4.68
15A	1/2 B	21.7	2.8	1.31	7.20
20A	3/4 B	27.2	2.8	1.68	9.24
25A	1 B	34.0	3.2	2.43	13.4
32A	1 1/4 B	42.7	3.5	3.38	18.6
40A	1 1/2 B	48.6	3.5	3.89	21.4
50A	2 B	60.5	3.8	5.31	29.2
65A	2 1/2 B	76.3	4.2	7.47	41.1
80A	3 B	89.1	4.2	8.79	48.3
90A	3 1/2 B	101.6	4.2	10.1	55.6
100A	4 B	114.3	4.5	12.2	67.1
125A	5 B	139.8	4.5	15.0	82.5
150A	6 B	165.2	5.0	19.8	109
175A	7 B	190.7	5.3	24.2	133
200A	8 B	216.3	5.8	30.1	166
225A	9 B	241.8	6.2	36.0	198
250A	10 B	267.4	6.6	42.4	233
300A	12 B	318.5	6.9	53.0	292
350A	14 B	355.6	7.9	67.7	372
400A	16 B	406.4	7.9	77.6	427
450A	18 B	457.2	7.9	87.5	481
500A	20 B	508.0	7.9	97.4	536

切断・開先加工も承ります。